

T10 LED TUBE LIGHT(120LM/W)

- ETL and RoHS listed
- Aluminum alloy + PC cover, Aluminum alloy PCB, good heat dissipation
- Input 100-277VAC wide voltage, suitable for industrial voltage
- LM 80 light source, low luminous decay, long life, 5 years warranty
- Whole light 120lm/W, CRI(Ra) > 80
- Base: FA8, G13, R17 for options



Specifications

Model No.	SNT10-18S	SNT10-24S
Length	6FT	8FT
Power	32W	36W
Voltage	100-277VAC	100-277VAC
Frequency	50-60Hz	50-60Hz
PF	>0.9	>0.9
THD	<14%	<14%
CCT	3000K,4000K,5000K	3000K,4000K,5000K
CRI(Ra)	80+	80+
Efficacy (clear)	120LM/W(5000K)	120LM/W(5000K)
Efficacy (frosted)	110LM/W(5000K)	110LM/W(5000K)
Lumens (clear)	3800LM(5000K)	4300LM(5000K)
Lumens (frosted)	3500LM(5000K)	4000LM(5000K)
LED Model	SMD2835	SMD2835
LED Quantity	168PCS	224PCS
Beam Angle (clear)	120°	120°
Beam Angle (frosted)	160°	160°
Operating Temp.	-40°-122°F	-40°-122°F
Lifespan	50,000H	50,000H
IP Rating	IP 40	IP 40
Warranty	5 years	5 years
Certificates	cETL,ETL,RoHS	cETL,ETL,RoHS
Installation(Base)	Type B(G13)	Type B(G13)
Product Size	L1814*Φ33mm	L2367*Φ33mm
Product N.W.	0.56KG	0.72KG
Packing Method	25PCS/box	25PCS/box
Pack Size	L1880*W230*H215mm	L2430*W230*H215mm
Carton G.W.	20.0KGS	26.0KGS



Applications

- Factories, Warehouses, Supermarkets
- Production lines, Corridors
- Conference rooms and other indoor places