

LED TUBE LIGHT- (CRI:>95, 110LM/W)

- DLC, ETL, RoHS and FCC listed
- Aluminum alloy + PC cover, Aluminum alloy PCB, good heat dissipation
- No strobe driver, whole light without flicker
- Input 100-277VAC wide voltage, suitable for industrial voltage
- LM 80 light source, low luminous decay, long life, 5 years warranty
- Adopt high revivification design, CRI(Ra):>95 restore original color



Ra:95+

Specifications

Model No.	SNT8B-06S	SNT8B-09S	SNT8B-12S	SNT8B-15S
Length	2FT	3FT	4FT	5FT
Power	9W	14W	18W	22W
Voltage	100-277VAC	100-277VAC	100-277VAC	100-277VAC
Frequency	50-60Hz	50-60Hz	50-60Hz	50-60Hz
PF	>0.9	>0.9	>0.9	>0.9
THD	<14%	<14%	<14%	<14%
CCT	3000K,4000K,5000K	3000K,4000K,5000K	3000K,4000K,5000K	3000K,4000K,5000K
CRI(Ra)	95+	95+	95+	95+
Efficacy (clear)	110LM/W(5000K)	110LM/W(5000K)	110LM/W(5000K)	110LM/W(5000K)
Efficacy (frosted)	100LM/W(5000K)	100LM/W(5000K)	100LM/W(5000K)	100LM/W(5000K)
Lumens (clear)	1000LM(5000K)	1500LM(5000K)	2000LM(5000K)	2400LM(5000K)
Lumens (frosted)	900LM(5000K)	1400LM(5000K)	1800LM(5000K)	2200LM(5000K)
LED Model	SMD2835	SMD2835	SMD2835	SMD2835
LED Quantity	60PCS	72PCS	120PCS	168PCS
Beam Angle (clear)	120°	120°	120°	120°
Beam Angle (frosted)	160°	160°	160°	160°
Operating Temp.	-40°-122°F	-40°-122°F	-40°-122°F	-40°-122°F
Lifespan	50,000H	50,000H	50,000H	50,000H
IP Rating	IP 40	IP 40	IP 40	IP 40
Certificates	ETL,FCC,RoHS	ETL,FCC,RoHS	DLC,ETL,FCC,RoHS	ETL,FCC,RoHS
Warranty	5 years	5 years	5 years	5 years
Installation (Base)	Type B(G13)	Type B(G13)	Type B(G13)	Type B(G13)
Product Size	L588*Φ26mm	L895*Φ26mm	L1198*Φ26mm	L1498*Φ26mm
Product N.W.	0.18KG	0.26KG	0.33KG	0.40KG
Packing Method	25PCS/box	25PCS/box	25PCS/box	25PCS/box
Pack Size	L650*W180*H180mm	L960*W180*H180mm	L1260*W180*H180mm	L1560*W180*H180mm
Carton G.W.	6.0KGS	9.0KGS	11.0KGS	14.0KGS

Applications

- Residential areas
- Factories, hotels
- Clothing stores
- Fruit shops
- Supermarkets, etc.