

360°Light Emission LED Tube Light(150LM/W)



- **360°** light emission
- High light efficacy, 150lm/W
- Good heat radiation
- IP54 rating, can be used in wet conditions
- Highlight 2835 LED
- LM 80 light source, low luminous decay, long life, 5 years warranty



150LM/W(5000K)

Applications

- Factories, Warehouses, Supermarkets
- Production lines, Corridors
- Conference rooms and other indoor places

Specifications

Model No.	SNT12-4FT	SNT12-5FT	SNT12-6FT	SNT12-8FT
Length	4FT	5FT	6FT	8FT
Power	32W	32W	48W	64W
Voltage	100-277VAC	100-277VAC	100-277VAC	100-277VAC
Frequency	50-60Hz	50-60Hz	50-60Hz	50-60Hz
PF	>0.9	>0.9	>0.9	>0.9
THD	<23%	<23%	<23%	<23%
CCT	3000K,4000K,5000K	3000K,4000K,5000K	3000K,4000K,5000K	3000K,4000K,5000K
CRI(Ra)	80+	80+	80+	80+
Efficacy	150LM/W(5000K)	150LM/W(5000K)	150LM/W(5000K)	150LM/W(5000K)
Lumens	4800LM(5000K)	4800LM(5000K)	7200LM(5000K)	9600LM(5000K)
LED Model	SMD2835	SMD2835	SMD2835	SMD2835
LED Quantity	480PCS	480PCS	720PCS	960PCS
Beam Angle	360°	360°	360°	360°
Operating Tmp.	-40°-122°F	-40°-122°F	-40°-122°F	-40°-122°F
Lifespan	50,000H	50,000H	50,000H	50,000H
IP Rating	IP 54	IP 54	IP 54	IP 54
Warranty	5 years	5 years	5 years	5 years
Installation(Base)	Type B(G13)	Type B(G13)	Type B(G13)	Type B(G13)
Product Size	L1198*Φ38mm	L1498*Φ38mm	L1814*Φ38mm	L2367*Φ38mm
Product N.W.	0.60KG	0.75KG	0.90KG	1.20KG
Packing Method	12PCS/box	12PCS/box	12PCS/box	12PCS/box
Pack Size	L1260*W190*H150mm	L1460*W190*H150mm	L1880*W190*H150mm	L2430*W190*H150mm
Carton G.W.	9.0KGS	11.5KGS	14.0KGS	18.0KGS