

## SN- IPAD LED Flood Light



- UL and RoHS Listed
- IP65 Rating
- Adopt ADC12 die-casting aluminum to reach heat dissipation, increase the area of aluminum PCB, thus increase light-emitting area, the whole lamp has stability of excellent heat dissipation
- Proprietary mold design, simple and elegant, lighter, thinner, reach to excellent decorative effect, simple installation, easy disassembly
- Powder coated treatment, corrosion-resistant
- Adopt tempered glass, emits soft light, safe to us, transmittance rate  $\geq 90\%$
- 10W/20W/30W/50W for options



## Specifications

Model No.	SN-PFL-10Ag-000	SN-PFL-20Ag-000	SN-PFL-30Ag-000	SN-PFL-50Ag-000
Power	10W	20W	30W	50W
Efficacy	$\geq 90\text{LM/W}$	$\geq 90\text{LM/W}$	$\geq 90\text{LM/W}$	$\geq 90\text{LM/W}$
Lumens	$\geq 900\text{LM}$	$\geq 1800\text{LM}$	$\geq 2700\text{LM}$	$\geq 4500\text{LM}$
LED Model	SMD2835	SMD2835	SMD2835	SMD2835
LED Quantity	20PCS	44PCS	60PCS	100PCS
Voltage	120-270VAC	120-270VAC	120-270VAC	120-270VAC
Frequency	50-60Hz	50-60Hz	50-60Hz	50-60Hz
PF	>0.5	>0.9	>0.9	>0.9
CCT	4000K,5000K,6000K	4000K,5000K,6000K	4000K,5000K,6000K	4000K,5000K,6000K
CRI	>70	>70	>70	>70
Material	ADC12	ADC12	ADC12	ADC12
Driver	Lang Ke	Lang Ke	Lang Ke	Lang Ke
Beam Angle	110°	110°	110°	110°
Warranty	2 years	2 years	2 years	2 years
Certificates	UL,RoHS	UL,RoHS	UL,RoHS	UL,RoHS
IP Rating	IP 65	IP 65	IP 65	IP 65
Storage Temp.	-40°-176°F	-40°-176°F	-40°-176°F	-40°-176°F
Working Temp.	-20°-140°F	-20°-140°F	-20°-140°F	-20°-140°F
N.W.	0.47KG	0.91KG	1.40KGS	1.79KGS
G.W.	0.50KG	0.96KG	1.47KGS	1.90KGS

## Applications

- Widely used in outdoor and indoor lighting
- Such as for stadium
- Parking Lots
- Airports
- Terminals
- Huge Buildings
- Billboards