

LED Tri-Proof Light

- Waterproof, dust proof, IP65 Rating, anti-corrosion, WF2 level
- Aluminum+PC design, housing is insulated, no electric shock risk when using
- Adopt high quality isolated no strobe LED driver, reduce the damage from light to the eyes
- Various colors are available, fashionable
- Lifespan > 50000H(LM70 standard), save 80% energy
- 5 years warranty



Specifications

| Model No. | TRA-2FT-A1 | TRA-4FT-A1 | TRA-5FT-A1 |
|-----------------|-------------------|-------------------|-------------------|
| Length | 2FT | 4FT | 5FT |
| Power | 20W | 40W | 60W |
| Voltage | 100-277VAC | 100-277VAC | 100-277VAC |
| Frequency | 50-60Hz | 50-60Hz | 50-60Hz |
| PF | >0.9 | >0.9 | >0.9 |
| THD | <23% | <23% | <23% |
| CCT | 3000K,4000K,5000K | 3000K,4000K,5000K | 3000K,4000K,5000K |
| CRI(Ra) | 80+ | 80+ | 80+ |
| Efficacy | 130LM/W(5000K) | 130LM/W(5000K) | 120LM/W(5000K) |
| Lumens | 2600LM(5000K) | 5200LM(5000K) | 7200LM(5000K) |
| LED Model | SMD2835 | SMD2835 | SMD2835 |
| LED Quantity | 180PCS | 300PCS | 360PCS |
| Beam Angle | 150° | 150° | 150° |
| Operating Temp. | -40°-122°F | -40°-122°F | -40°-122°F |
| Lifespan | 50,000H | 50,000H | 50,000H |
| IP Rating | IP 65 | IP 65 | IP 65 |
| Warranty | 5 years | 5 years | 5 years |
| Installation | Suspended | Suspended | Suspended |
| Product Size | L600*W97*H85mm | L1200*W97*H85mm | L1500*W97*H85mm |
| Product N.W. | 1.6KGS | 2.9KGS | 3.4KGS |
| Packing Method | 6PCS/box | 6PCS/box | 6PCS/box |
| Pack Size | L700*W340*H215mm | L1300*W340*H215mm | L1600*W340*H215mm |
| Carton G.W. | 12KGS | 21KGS | 25KGS |

Applications

- Railway
- Electricity
- Metallurgy
- Oil
- Petrochemical and various types of factories
- Workshops
- Field stations and major facilities
- Stadiums and other places

